

## Tuffstuff Building Wrap

Aluminium foil bonded to a polymer based weave of high tensile and tear strength. The blue face of the weave reduces any problems with reflected glare during installation.

### Applications

- FRAMECAD Tuffstuff is an Extra Heavy Duty wall wrap recommended for residential and commercial buildings.

### Features & Benefits

- When used in conjunction with an airspace it is an effective thermal insulation material because of the high reflectivity and low emissivity of its aluminium foil surfaces.
- Provides an effective barrier against moisture, vapours, wind, heat and dust penetration when overlapped and sealed with self adhesive aluminium tape.

### Specifications

- It complies with the requirements of AS/NZS4200.1 for "Pliable Building Membranes".
- It has a low flammability index (not greater than 5) in accordance with AS1530.2.
- It is classified High as Vapour Barrier in accordance with AS/NZS4200.1.
- It is classified High as Water Barrier in accordance with AS/NZS4200.1.
- it is classified Reflective for emissivity in accordance with AS/NZS4200.1.

FRAMECAD Cladding & Lining  
is distributed by:  
Bon Pacific Trading Limited  
PO Box 1292  
Auckland 1140, New Zealand

**P** +64 9 377 6640  
**F** +64 9 307 7139  
**E** info@bonpac.com  
[www.bonpac.com](http://www.bonpac.com)

ROLL SIZES			
Type	Roll Length (m)	Roll Width (mm)	Square Meter
Heavy Duty	60	1500	90
	60	1350	81

### Installation

- FRAMECAD TuffStuff should be installed with a 150mm overlap between runs. To achieve the stated Total R-values a minimum air space of 40mm is required adjacent to each reflective foil face.
- Do not allow contact with wet mortar or concrete: alkalis' attack aluminium foil.

### Manufacturing Classification

- Manufactured under an ISO9001 certified quality management system.

